

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 58-083184

(43)Date of publication of application : 18.05.1983

(51)Int.Cl.

F28D 15/00

(21)Application number : 56-181467

(71)Applicant : AKACHI HISATERU

(22)Date of filing : 12.11.1981


(72)Inventor : AKACHI HISATERU

## (54) HEAT PIPE

### (57)Abstract:

**PURPOSE:** To enhance heat response property and reduce loss, by a method wherein a heat pipe is provided with one pipe end surface as a heat input surface and the other pipe end surface as a heat output surface, flat inside surfaces of both end sealing plates are reinforced by a plurality of parallel fins, and ends of grooves formed between the fins make contact with the inside wall of a heat pipe container.

**CONSTITUTION:** The end sealing plate 1 on the heat output surface side and the end sealing plate 2 on the heat input surface side which constitute both ends of the heat pipe container 3 are constituted of a plurality of parallel fins, the plate 1 makes contact with a heat sink 6, and the plate 2 makes contact with a heating element 8. A hollow pipe 4 is provided between the end sealing plates 1 and 2 to reinforce the plates 1, 2 and promotes the recirculation of a working fluid. Since the parallel fins are used as end sealing plates, heat-exchanging efficiency is enhanced, flow resistance of the fluid is reduced, and the recirculating speed of the fluid is enhanced.



## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of

PAT-NO: JP358083184A  
DOCUMENT-IDENTIFIER: JP 58083184 A  
TITLE: HEAT PIPE  
PUBN-DATE: May 18, 1983

INVENTOR-INFORMATION:  
NAME

AKACHI, HISATERU

ASSIGNEE-INFORMATION:  
NAME

COUNTRY

AKACHI HISATERU

N/A

APPL-NO: JP56181467  
APPL-DATE: November 12, 1981

INT-CL (IPC): F28D015/00

US-CL-CURRENT: 165/104.21, 165/104.33

ABSTRACT:

PURPOSE: To enhance heat response property and reduce loss, by a method wherein a heat pipe is provided with one pipe end surface as a heat input

surface and the other pipe end surface as a heat output surface, flat inside surfaces of both end sealing plates are reinforced by a plurality of parallel fins, and ends of grooves formed between the fins make contact with the inside wall of a heat pipe container.

CONSTITUTION: The end sealing plate 1 on the heat output surface side and the end sealing plate 2 on the heat input surface side which constitute both ends of the heat pipe container 3 are constituted of a plurality of parallel fins, the plate 1 makes contact with a heat sink 6, and the plate 2 makes contact with a heating element 8. A hollow pipe 4 is provided between the end sealing plates 1 and 2 to reinforce the plates 1, 2 and promotes the recirculation of a working fluid. Since the parallel fins are used as end sealing plates, heat-exchanging efficiency is enhanced, flow resistance of the fluid is reduced, and the recirculating speed of the fluid is enhanced.

COPYRIGHT: (C)1983, JPO&Japio